Nebula

SPECIFICATION DOCUMENT









Overview

Suspended panel light with a unique design offering a 360 degree beam lighting effect. The 60W suspended office light delivers up to 6482 lumens spreading in all directions, comes in 3000K or 4000K and comes with a magnetic box for ease of installation.



Finish: White

Power: 60W

Kelvin: 3000K 4000K


360° Spread Light:







Technical Drawings



Overview

Applications	Interior	
Construction Material	Aluminium	
Diffuser Type	PMMA	
IP Rating	IP20	
Mounting	Suspended	
Weight (kg)	4.5	
Ambient Temperature	-20°C to +45°C	
Warranty	5 years	

Luminaire Output

Colour Temperature	3000K 4000K	
CRI	>80 Ra	
Efficacy	108 Lm/W	
Beam Angle	360°	
Operating Hours	50,000	
Macadam Ellipse	≤6 sdcm	
LEDs	SMD4014	

Supply & Power

Voltage Range	AC220-240V
Power Factor	>0.90
Inrush Current	0.29A
Protection Class IEC	Class I
Driver	Remote (in the ceiling plate)
Cable entry	Back

Product Codes & Specifications

Code	Kelvin	Lumens (lumen spread is 50%-50% up-down)
R101801/3K/60W	3000K	6136
R101801/4K/60W	4000K	6482





Photometry

