Salus II

SPECIFICATION DOCUMENT









Overview

Emergency bulkhead exit sign with IP65 body. The ultra-slim profile LED polycarbonate bulkhead can also be recessed and there is a hinged screwless gear tray for ease of installation.





Finish:

White

Power:

3W

Kelvin:


6500K








Technical Drawings





Overview

Applications	Interior/Exterior
Base	ABS
Diffuser Type	Polycarbonate
IP Rating	IP65
Mounting	Surface, recessed, Suspended
Weight (kg)	0.60
Warranty	3 years

Luminaire Output

Colour Temperature	6500K
Beam Angle	120°
Operating Hours	30,000
CRI	>80 Ra
Self-test	Yes
Manual test	Yes

Supply & Power

Voltage Range	AC220-240V
Power Factor	0.40
Inrush Current	4.96A
Running Current	32mA
Protection Class IEC	Class I
Ambient Temperature	5°C to +40°C

Product Codes & Specifications

Code	Lumens
R231201	150







Options

Suffix	Option
/NL	No legends
/E-Z10	Z10 Remote control integral emergency

Additional Accessories

Code	Accessory
R23-01	Semi-recessed frame
R23-02	Salus II IP65 ceiling exit sign kit
R10-Z10	Z10 Emergency remote control

Installation example

55 Queen Street Apartments, Manchester, UK

